

Stellana Focus

Resilient Tire

Superior economy resilient tires for indoor and outdoor applications.

Key Attributes Include:

- Multi-layer construction
- Superior heat dissipation
- Low vibration
- High driver comfort
- Economically priced

www.polmertyres.cz

POLMER
TYRES

Focus For Standard Applications

This tire's unique construction offers superior comfort and performance when compared to competing budget tires. The durable multi-layer construction includes a balanced cushion layer between the tire's tread and base layers. This layer provides an additional level of heat dissipation compared to two-layer resilient tires. Available in both black and non-marking options, the Focus delivers excellent performance in standard to light material handling applications.



Durable multi-layer construction that is superior to a dual layer tire

Key Attributes

- High performance tread reduces chunking and tearing in indoor and outdoor applications.
- Small cushion layer to improve heat dissipation and rider comfort.
- The extremely hard base is reinforced by steel beads for added strength, flexibility, and to prevent rotation on the rim.



Lock

Standard

Available Tire Sizes

No	Tire No.	Rim	Approx. Tire Qty. Per 20' FCL	Tread Width mm	Max Overall width mm	Overall Diameter (+/- 2%) mm	ETRTO Standards				
							Counter Balanced Lift Trucks		Other Vehicles Up to		
							Up to 25km/h		25km/h	10km/h	6km/h
						Load Wheels	Steering Wheels				
1	4.00x8	3.00D-8	1,600	97	113	408	950	730	730	860	950
2	140/55-9	4.00 E-9	1,400	106	128	378	1170	900	900	1060	1170
3	5.00x8	3.00D-8	1,060	99	122	457	1415	1090	1090	1285	1415
4	5.00x8	3.25I-8	1,060	99	122	457	1415	1090	1090	1285	1415
5	15x4 1/2-8	3.00D-8	1,900	88	106	380	1040	800	800	945	1040
6	16x6-8	4.33R-8	1,200	120	141	420	1495	1150	1150	1360	1495
7	18x7-8	4.33R-8	900	126	154	453	2145	1650	1650	1945	2145
8	6.00-9	4.00E-9	700	109	140	525	1885	1450	1450	1710	1885
9	21x8-9	6.00E-9	650	153	183	525	2755	2120	2120	2500	2755
10	6.50-10	5.00F-10	520	129	161	572	2340	1800	1800	2125	2340
11	200/50-10	6.50F-10	900	156	186	456	2470	1900	1900	2240	2470
12	23x9-10	6.50F-10	400	164	199	587	3445	2650	2650	3125	3445
13	7.00-12	5.00S-12	375	137	171	652	2920	2240	2240	2645	2920
14	7.00-15	5.5-15	300	139	177	720	3545	2725	2725	3215	3545
15	27x10-12	8.00G-12	265	203	239	670	3900	3000	3000	3540	3900
16	28x9-15	7.0-15	285	184	219	678	3900	3000	3000	3540	3900
17	250-15	7.0-15	220	182	221	720	4745	3650	3650	4310	4745
18	250-15	7.5-15	220	182	221	720	4745	3650	3650	4310	4745
19	8.25-15	6.5-15	160	162	205	814	4750	3650	3650	4300	4750
20	300-15	8.0-15	150	213	253	818	5850	4500	4500	5310	5850
21	23X10-12	8.00G-12	300	206	238	580	3770	2900	2900	3420	3770
22	10.00-20	7.0-20	80	250	284	1016	6000	5000	5000	5450	6000
23	10.00-20	7.5-20	80	250	284	1016	6000	5000	5000	5450	6000
24	10.00-20	8.0-20	80	250	284	1016	6000	5000	5000	5450	6000

Normal & lock versions available for all sizes except 10.00-20 (Only normal rim version for 10.00-20)

Regular Tires

6.00 - 9
 $d = 9"$ (Rim Diameter)
 $W = 6"$ (Max Width)

Wide Tires (High Section Width)

200 / 50 - 10
 $d = 10"$ (Rim Diameter)
 $AR = 0.50$ (Nominal Aspect Ratio - H/S)
 $D = 200$ mm (Max Width)

High Load Tires

300 - 15
 $d = 15"$ (Rim Diameter)
 $W = 330$ mm (Max Width)

Wide Tires

18 x 7 - 8
 $d = 8"$ (Rim Diameter)
 $W = 7"$ (Max Width)
 $D = 18"$ (Overall Diameter)

POLMER TYRES, spol. s r.o.

Říčanská 1248
 763 12 Vizovice
 Česká republika

tel.: +420 604 548 819
 e-mail: info@polmertyres.cz
 web: www.polmertyres.cz

